

TECHNICAL SPECIFICATIONS OF GENTS SAFETY SHOE

DESCRIPTION	SPECIFICATION
Brand & Article	JCB HEATMAX (High Ankle Nitrile Rubber Safety Footwear)
Operative Standard	Meets IS 15298: 2016 Part II
Description	Black 4 Eyelet Ankle Boot, Vulcanised Nitrile Rubber Sole Electric Shock Resistant. As per Design B.
Sizes	UK (Range 5-12)
Height & Size Of Shoe	More Than 118 mm But Less Than 173 mm For Size 8 (+/- 5mm)
Color	Black
Marking	As Per IS 15298 (Part 2) : 2016 Clause 7 ISI Marked.
Electrical Properties	Electrical Shock resistance (EH) 14 kv
Upper Leather	Printed Grain Buff Apollo Textured Leather.
Vamp Lining	Non Woven Polyester 250 GSM
Tongue & Collar	Padded Leather
Lining Other Than Vamp	Black Cambrelle
Socks	Full EVA Padded.
Insole	Leather Board, Non Antistatic
Out Sole	Nitrile Rubber, Black
Sole Fixation	Direct Vulcanised.
Heel Stiffener	Molded Stiffener For Additional Support.
Upper/ Outsole Bond Strength	As Per 5.3.1.2 Of Is 15298 (Part 2):2016
Impact Resistance Of Toe Cap	As Per 5.3.2.3 Of Is 15298 (Part 2):2016
Upper Thickness	As Per 5.4.2 Of Is 15298 (Part 2):2016
Upper Tear Strength	As Per 5.4.3 Of Is 15298 (Part 2):2016
Upper Ph Value	As Per 5.4.7 Of IS 15298 (Part 2):2016
Quarter Lining Tear Strength	As Per 5.5.1 Of Is 15298 (Part 2):2016
Sole Abrasion Resistance	As Per 5.8.3 Of Is 15298 (Part 2):2016
Sole Flexing Resistance	As Per 5.8.4 Of Is 15298 (Part 2):2016
Energy Absorption Of Seat	As Per 6.2.4 Of Is 15298 (Part 2):2016
Resistance To Hot Contact 300°C	As Per 6.4.1 Of Is 15298 (Part 2):2016
Resistance To Fuel Oil	As Per 6.4.2 Of IS 15298 (Part 2):2016
200j Rust Resistant Steel Toe Cap	En 12568 Marked With Polymer Comfort Strip. Also Protect Against Compression Injury Up To 15 Kn.
Thread	Polyester/ Nylon
Lace	Round Polymer With Hardened Tips
Branding On Upper	JCB Two Colored Polymer Label On Outer Side
Branding On Socks	JCB Fabric Woven Label On Heel Area Of The Socks
Marking On The Sole	Date & Size Clock
Suitable For	Acidic Area & Hot Surface.



Sole Licensee In India
Rahman Industries Limited
310, Krishna Towers,15/63, Civil Lines
Kanpur – 208001 INDIA
PH: + 91512- 2330601
Mo:- 9336811103 & 9336110112
Email:- kt@rahman-group.com