

TECHNICAL SPECIFICATIONS OF LADIES SAFETY SHOE STEEL TOE CAP

DESCRIPTION	SPECIFICATIONS
BRAND & ARTICLE	JCB COUNTESS (LADIES LOW ANKLE SAFETY FOOTWEAR)
Operative Standard	Meets IS15298: 2016 Part II
Description	Light Weight Black, low ankle, Velcro Fastener Single Density, Slip Resistant, Direct Injected (on DESMA) PU Sole, Safety Footwear. Nail less As per Design Strobel Construction.
SIZES	UK (Range 2 -8)
Height & size of shoe	More than 113 mm but less than 178 mm for size 8 (+/- 5mm)
Color	BLACK
Marking	As per IS 15298 (Part 2):2016 Clause 7.
Electrical Properties	Antistatic. Resistance between 100 Kilo Ohms & 1000 Mega Ohms
Upper leather	Black Grain Hair cell Leather
Vamp lining	Non Woven Polyester 250 GSM
Tongue & Collar	Padded Leather
Lining other than vamp	MESH LINING Gray
Socks	Full EVA Molded ANTISTATIC. BEAR JCB Fabric LABEL
Insole	Non Woven Antistatic more than 2 mm thick
Out Sole	PU Single density Black in Color
Sole fixation	Direct injection process on DSMA Machines
HEEL STIFFNER	Molded stiffener for additional support.
Upper/ Outsole Bond Strength	As per 5.3.1.2 of IS 15298 (Part 2) : 2016
Impact Resistance Of Toe Cap	As per 5.3.2.3 of IS 15298 (Part 2) : 2016
Upper Thickness	As per 5.4.2 of IS 15298 (Part 2) : 2016
Upper Tear Strength	As per 5.4.3 of IS 15298 (Part 2) : 2016
Upper pH Value	As per 5.4.7 of IS 15298 (Part 2) : 2016
Quarter Lining Tear Strength	As per 5.5.1 of IS 15298 (Part 2) : 2016
Sole Abrasion Resistance	As per 5.8.3 of IS 15298 (Part 2) : 2016
Sole Flexing Resistance	As per 5.8.4 of IS 15298 (Part 2) : 2016
Antistatic Footwear	As per 6.2.2.2 of IS 15298 (Part 2) : 2016
Energy Absorption Of Seat	As per 6.2.4 of IS 15298 (Part 2) : 2016
Resistance To Hot Contact	As per 6.4.1 of IS 15298 (Part 2) : 2016
Resistance to Fuel Oil	As per 6.4.2 of IS 15298 (Part 2) : 2016
200J Rust Resistant Steel Toe Cap	EN 12568 Marked imported with polymer comfort strip. Also protect against compression injury up to 15 KN.
Thread	NYLON / Polyester
FASTENER	Two Leather Strip with Black Velcro
Branding on Upper	JCB two colored Polymer Label on outer side
Branding on Socks	JCB Fabric woven label on heel area of the socks
MARKING ON THE SOLE	DATE & SIZE CLOCK
SUITABLE FOR	ENGINEERING, PETROCHEMICAL & CONSTRUCTION



310 Krishna Towers, 15/63,
Civil Lines, KANPUR 208001
09336110112 & 09336811103
info@jcbfootwear.in
www.jcbfootwear.in