

LEATHER

130°C Sole

200J ST

Size 5-12

130°C SOLE
S1 SRA

EXCAVATOR

Full Grain Apollo Leather
Double Density DIP PU Sole
Padded Tongue & Collar
Grey+Orange Mesh Lining
4 Metal D Rings+1 Hooks
Antistatic 35J Heel
Light Weight

130°C SOLE
S1 SRA


TREKKER

Nubuck Leather Upper
Double Density DIP PU Sole
Padded Tongue & Collar
Grey+Orange Mesh Lining
4 Hexagonal Eyelets+2 Hooks
Antistatic 35J Heel
Light Weight

130°C SOLE
O1 SRC

SPEEDMAX

Full Grain Texture Leather
Thermoplastic Toe Stiffener
Double Density PU+PU Sole
Padded Tongue & Collar
Mesh Lining 35J Heel
Velcro Fastener
Antistatics

ELECTRICAL
ACID ALKALI350°C SOLE
S1 SRA

HEATMAX

Full Grain Apollo Leather
Single Density DIP Nitrile Sole
Padded Tongue & Collar
Grey Mesh Lining 25J Heel
4 Metal D Rings+1 Hooks
15Kv Electrical

ELECTRICAL
ACID ALKALI350°C SOLE
S1 SRA

HEATKING

Full Grain Apollo Leather
Single Density DIP Nitrile Sole
Padded Tongue & Collar
Grey Mesh Lining 25J Heel
4 Metal D Rings+1 Hooks
15Kv Electrical



In every corner of the world you'll find a JCB machine. Since our beginnings in 1945, we have always invested heavily in research & development, keeping JCB at the cutting edge of innovation. The same innovation to always get the job done better, the same quality to never let you down, the same engineering heritage & expertise that you can trust, can be found in JCB Safety Footwear.

Labelling

Identification brand	JCB	ISI MARK
Article number	GUTSO	
Size	UK8	Manufacture identification
Standard number(s)	ISO 20345:2011 IS 15298(PART2):2016	
Symbol for protection	S1 SRC A HI CI E FO	Additional requirements

Leather Footwear Symbols for Industrial Usage

Basic /additional requirements /categories	SAFETY FOOTWEAR EN ISO 20345 IS 15298(PART2):2016	OCCUPATIONAL FOOTWEAR EN ISO 20347 IS 15298(PART4):2017
Basic requirements for shoes and impact resistance of toe caps	SB 200 Joule	OB No requirement
Additional requirements: Closed seat region Antistatic properties (A) Energy absorption of seat region (E) Fuel oil resistance (FO)	S1	O1
S1+ water penetration & absorption (WRU)	S2	O2
S2+: Penetration resistance (P) Cleated outsole	S3	O3
The choice of a footwear depends on the type of hazard. As with all footwear, additional requirements may exist (e.g. penetration resistance or electrical resistance including ESD. These footwear are then marked accordingly. The testing methods are specified in ISO 20344/ IS 15298(Part1).		

OPTION :
Conductive; ESD; EH
Penetration Resistant Sole
Water Resistant Upper
O1

www.jcbfootwear.in

JCB

310 Krishna Tower, 15/63,
Civil Lines, Kanpur 208001 INDIA
info@jcbfootwear.in
kt@jcbfootwear.in



JCB
SAFETY FOOTWEAR

**BORN TOUGH
BUILT RELIABLE**

IS 15298
(PART 2)
CM/L-4867488

www.jcbfootwear.in

Apollo

200J ST

ANTISTATIC

35J Heel

Size 5-12

LEATHER

200J ST

ANTISTATIC

130°C Sole

Size 5-12

200J ST

ANTISTATIC

130°C Sole

35J Heel

Size 5-12

DRONE

Single Density DIP PU Sole
Padded Tongue & Collar
Grey Mesh Lining
Reflective Strip
4 Metal Eyelets
Fuel Oil/Chemical Resistant
Super Light Weight



130°C SOLE
S1 SRC

GUTSO

Double Density DIP PU Sole
Padded Tongue & Collar
Grey+Orange Mesh Lining
Reflective Strip
4 Metal Eyelets
Fuel Oil/Chemical Resistant
Super Light Weight



130°C SOLE
S1 SRC

EARTHMOVER

Double Density DIP PU Sole
Padded Tongue & Collar
Grey+Orange Mesh Lining
4 Metal Eyelets
Fuel Oil/Chemical Resistant
Light Weight



130°C SOLE
S1 SRC

SITEMASTER

Double Density DIP PU Sole
Padded Tongue & Collar
Grey+Orange Mesh Lining
4 Metal Eyelets
Fuel Oil/Chemical Resistant
Light Weight



130°C SOLE
S1 SRC

MIGHTY

Double Density DIP PU Sole
Padded Tongue & Collar
Grey+Orange Mesh Lining
5 Eyelets
Fuel Oil/Chemical Resistant
Light Weight



130°C SOLE
S1 SRC

COMPOSITE
TOE CAP 200J

ALL-TERRAIN

Double Density DIP PU+ Nitrile
Full Grain Apollo Leather
Padded Tongue & Collar
Grey+Orange Mesh Lining
5 Metal Eyelets 35J Heel
Fuel Oil/ Acid/Alkali Resistant
HRO
Light Weight



350°C SOLE
S1 SRC

COMPOSITE
TOE CAP 200J

EXEC

Double Density DIP PU+PU
Full Grain CG Plain Leather
Padded Tongue & Collar
Black Mesh Lining
4 Hidden Eyelets 35J Heel
Fuel Oil/Chemical Resistant



S1 SRC

BROGUE

VENT

Suede Leather + Scuff Cap
Double Density DIP PU+PU
Padded Tongue & Collar
Grey+Orange Mesh Lining
5 Metal Eyelets 35J Heel
Fuel Oil/Chemical Resistant
Light Weight



S1 SRC

ECOBOOST

Suede Leather
Single Density DIP PU
Padded Tongue & Collar
Grey Mesh Lining
4 Eyelets 35J Heel
Fuel Oil/Chemical Resistant
Light Weight



S1 SRC

Size 2-8

COUNTESS

Full Grain CG Plain Leather
Single Density DIP PU
Padded Tongue & Collar
Grey Mesh Lining
Velcro Fastener 35J Heel
Fuel Oil/Chemical Resistant
Light Weight



S1 SRC

LADIES

ACCESS

Full Grain Apollo Leather
Single Density DIP PU
Padded Tongue & Collar
Grey Mesh Lining
Velcro Fastener
Fuel Oil/Chemical Resistant
Light Weight



S1 SRC

HYDROMASTER

Micro-Fiber Upper Quick Drying
Single Density DIP PU
Padded Collar
Elastic Gusset-Slip On
Fuel Oil/Chemical Resistant
Light Weight
Option: ESD, All White



S1 SRC

WATER RESISTANT

POWERBOOM

High Tenacity Fly-net Upper
Padded Tongue & Collar
Black Mesh Lining
5 Eyelets
Fuel Oil/Chemical Resistant
Light Weight
Highly Comfortable



S1 SRC

HIGHLY BREATHABLE

FASTRAC

High Tenacity Fly-net Upper
Padded Tongue & Collar
Black Mesh Lining
5 Eyelets
Fuel Oil/Chemical Resistant
Light Weight
Highly Comfortable



S1 SRC

HIGHLY BREATHABLE

LOADALL

Full Grain Printed Leather
Double Density DIP PU Sole
Padded Tongue & Collar
Grey+Orange Mesh Lining
4 Metal Eyelets+2 Hooks
Fuel Oil/Chemical Resistant
Light Weight



S1 SRC